

TECHNICAL DATA SHEET



CPP 0202 – 1K ACRYLIC SMART CLEAR

DESCRIPTION

1K ACRYLIC SMART CLEAR is a crystal clear 1K, ready to use clear coat. Used for finishing coated surfaces in order to achieve a high gloss, UV resistant, durable finish.

1K ACRYLIC SMART CLEAR is a new high performance clear coat that gives 2K performance with the convenience of single pack. 1K ACRYLIC SMART CLEAR is the ultimate smart repair tool with excellent build, flow out and gloss retention. Compatible with most paint systems inc. water based.

The cured clear has excellent gloss and image depth and is ideal for spot repairs and complete resprays resulting in a durable, UV resistant finish.

1K ACRYLIC SMART CLEAR is isocyanate free.

SPRAY PRESSURE

30 PSI (2 bar) at the gun.

GUN SET-UP

1.4 - 1.6 compliant spray gun.

APPLICATION

Spray 2-3 normal coats with 5-10 min flash-off between coats.

DRYING

At 20°C the film is dust dry after approximately 30-40 min may be handled with care after approximately 4 hours. Full hardness is reached after approximately 24 hours.

At 60°C the film is dust dry at approximately 10-15 min may be handled with care after approximately 30-60 min.

FLASH POINT

22°C - 32°C.

Churchill Paints Ltd.

Riverdane Rd, Eaton Bank Trading Estate, Congleton, Cheshire, United Kingdom

T: +44 (0)1260 290 666

F: +44 (0)1260 290 444

✉: sales@churchill-paints.co.uk

Website: <http://www.churchill-paints.com>

© CHURCHILL PAINTS 1994



TECHNICAL DATA SHEET

CPP 0202 – 1K ACRYLIC SMART CLEAR

STORAGE

Correctly stored material, in firmly closed original containers, has a shelf-life of over 1 year. Contents of opened containers should be used up quickly. Always replace cap immediately after use.

HEALTH & SAFETY

Please refer to relevant Health and Safety Data Sheet, reference no. HSDS 0202

NOTE

This data relates only to the product designated herein and does not apply to use in combination with any other materials or in any other process.
The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.
Our product range is under continuous development and therefore products and specifications are subject to change without notice.
This product is for professional use only.
All trademarks, registered trademarks, brands and product names respected.

Churchill Paints Ltd.

Riverdane Rd, Eaton Bank Trading Estate, Congleton, Cheshire, United Kingdom

T: +44 (0)1260 290 666

F: +44 (0)1260 290 444

✉: sales@churchill-paints.co.uk

Website: <http://www.churchill-paints.com>

© CHURCHILL PAINTS 1994