


URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Liquid paint. For industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
BERNARDO ECENARRO, S.A.
Ugarte Industrialdea, 147
20720 Azkoitia - Gipuzkoa - Spain
Phone.: +34 943 74 28 00 -
Fax: +34 943 74 06 03
msds@besa.es
<http://www.besa.es>
- 1.4 Emergency telephone number:** +34 943742800 (8:00-13:00) (14:30-17:30)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) n° 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Eye Irrit. 2: Eye irritation, Category 2, H319
Flam. Liq. 3: Flammable liquids, Category 3, H226
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317
- 2.2 Label elements:**
CLP Regulation (EC) n° 1272/2008:
Warning
- 
- Hazard statements:**
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects
Eye Irrit. 2: H319 - Causes serious eye irritation
Flam. Liq. 3: H226 - Flammable liquid and vapour
Skin Irrit. 2: H315 - Causes skin irritation
Skin Sens. 1A: H317 - May cause an allergic skin reaction
- Precautionary statements:**
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280: Wear protective gloves/protective clothing/eye protection/face protection
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment
- Supplementary information:**
EUH208: Contains Butanone oxime. May produce an allergic reaction
- Substances that contribute to the classification**
Cobalt bis(2-ethylhexanoate)
- 2.3 Other hazards:**
Non-applicable

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives, aggregates, pigments, plasticizers and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	Xylene (mixture of isomers) Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	ATP CLP00 25 - <50 %
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	Ethylbenzene Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	ATP ATP06 5 - <10 %
CAS: Non-applicable EC: 918-668-5 Index: Non-applicable REACH: 01-2119455851-35-XXXX	Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w) Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336 - Danger	Self-classified 5 - <10 %
CAS: 7429-90-5 EC: 231-072-3 Index: 013-002-00-1 REACH: 01-2119529243-45-XXXX	Aluminium powder (stabilised) Regulation 1272/2008 Flam. Sol. 1: H228; Water-react. 2: H261 - Danger	ATP ATP01 1 - <2,5 %
CAS: 78-83-1 EC: 201-148-0 Index: 603-108-00-1 REACH: 01-2119484609-23-XXXX	Isobutanol Regulation 1272/2008 Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	ATP CLP00 1 - <2,5 %
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	Butyl Acetate Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	ATP CLP00 0,25 - <0,5 %
CAS: 22464-99-9 EC: 245-018-1 Index: Non-applicable REACH: 01-2119979088-21-XXXX	2-ethylhexanoic acid, zirconium salt Regulation 1272/2008 Repr. 2: H361d - Warning	Self-classified 0,25 - <0,5 %
CAS: 96-29-7 EC: 202-496-6 Index: 616-014-00-0 REACH: 01-2119539477-28-XXXX	Butanone oxime Regulation 1272/2008 Acute Tox. 4: H312; Carc. 2: H351; Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger	ATP CLP00 0,25 - <0,5 %
CAS: 136-52-7 EC: 205-250-6 Index: Non-applicable REACH: 01-2119524678-29-XXXX	Cobalt bis(2-ethylhexanoate) Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 2: H361; Skin Sens. 1A: H317 - Warning	Self-classified 0,2 - <0,25 %
CAS: 111-76-2 EC: 203-905-0 Index: 603-014-00-0 REACH: 01-2119475108-36-XXXX	2-butoxyethanol Regulation 1272/2008 Acute Tox. 4: H302+H312+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	ATP CLP00 0,2 - <0,25 %
CAS: 34590-94-8 EC: 252-104-2 Index: Non-applicable REACH: 01-2119450011-60-XXXX	Dipropylene Glycol Methyl Ether Regulation 1272/2008	Not classified <0,2 %

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

Other information:

Identification	Specific concentration limit
Aluminium powder (stabilised) CAS: 7429-90-5 EC: 231-072-3	% (w/w) >=50: Flam. Sol. 1 - H228 % (w/w) >=40: Water-react. 2 - H261

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 4: FIRST AID MEASURES (continued)

By inhalation:

This product is not classified as hazardous through inhalation, however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or shower the person affected if necessary thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

Contains substances that react with water producing extremely flammable gases.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

DO NOT USE WATER TO CLEAN.

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
Maximum Temp.: 30 °C
Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

Identification		Environmental limits	
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m ³
	IOELV (STEL)	100 ppm	442 mg/m ³
	Year	2015	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	IOELV (8h)	100 ppm	442 mg/m ³
	IOELV (STEL)	200 ppm	884 mg/m ³
	Year	2015	
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	IOELV (8h)	20 ppm	98 mg/m ³
	IOELV (STEL)	50 ppm	246 mg/m ³
	Year	2015	
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	IOELV (8h)	50 ppm	308 mg/m ³
	IOELV (STEL)		
	Year	2015	

DNEL (Workers):

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	289 mg/m ³	289 mg/m ³	77 mg/m ³	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w) CAS: Non-applicable EC: 918-668-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	150 mg/m ³	Non-applicable
Aluminium powder (stabilised) CAS: 7429-90-5 EC: 231-072-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	3.72 mg/m ³
Isobutanol CAS: 78-83-1 EC: 201-148-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	310 mg/m ³
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	960 mg/m ³	960 mg/m ³	480 mg/m ³	480 mg/m ³
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	15.75 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	5 mg/m ³	Non-applicable
Butanone oxime CAS: 96-29-7 EC: 202-496-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	2.5 mg/kg	Non-applicable	1.3 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	9 mg/m ³	3.33 mg/m ³
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	0.2351 mg/m ³
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
	Inhalation	663 mg/m ³	246 mg/m ³	98 mg/m ³	Non-applicable
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	65 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	310 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	1.6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14.8 mg/m ³	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	1.6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w) CAS: Non-applicable EC: 918-668-5	Oral	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	32 mg/m ³	Non-applicable
Aluminium powder (stabilised) CAS: 7429-90-5 EC: 231-072-3	Oral	Non-applicable	Non-applicable	3.95 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Isobutanol CAS: 78-83-1 EC: 201-148-0	Oral	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	55 mg/m ³

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	859.7 mg/m ³	859.7 mg/m ³	102.34 mg/m ³	102.34 mg/m ³
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	Oral	Non-applicable	Non-applicable	7.9 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	7.9 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2.5 mg/m ³	Non-applicable
Butanone oxime CAS: 96-29-7 EC: 202-496-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	1.5 mg/kg	Non-applicable	0.78 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2.7 mg/m ³	2 mg/m ³
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	Oral	Non-applicable	Non-applicable	0.0558 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	0.037 mg/m ³
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Oral	13.4 mg/kg	Non-applicable	3.2 mg/kg	Non-applicable
	Dermal	44.5 mg/kg	Non-applicable	38 mg/kg	Non-applicable
	Inhalation	426 mg/m ³	123 mg/m ³	49 mg/m ³	Non-applicable
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Non-applicable	Non-applicable	1.67 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	37.2 mg/m ³	Non-applicable

PNEC:

Identification				
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	STP	6.58 mg/L	Fresh water	0.327 mg/L
	Soil	2.31 mg/kg	Marine water	0.327 mg/L
	Intermittent	0.327 mg/L	Sediment (Fresh water)	12.46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12.46 mg/kg
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9.6 mg/L	Fresh water	0.1 mg/L
	Soil	2.68 mg/kg	Marine water	0.01 mg/L
	Intermittent	0.1 mg/L	Sediment (Fresh water)	13.7 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	1.37 mg/kg
Aluminium powder (stabilised) CAS: 7429-90-5 EC: 231-072-3	STP	20 mg/L	Fresh water	Non-applicable
	Soil	Non-applicable	Marine water	Non-applicable
	Intermittent	Non-applicable	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
Isobutanol CAS: 78-83-1 EC: 201-148-0	STP	10 mg/L	Fresh water	0.4 mg/L
	Soil	0.0699 mg/kg	Marine water	0.04 mg/L
	Intermittent	11 mg/L	Sediment (Fresh water)	1.52 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.152 mg/kg
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	STP	35.6 mg/L	Fresh water	0.18 mg/L
	Soil	0.0903 mg/kg	Marine water	0.018 mg/L
	Intermittent	0.36 mg/L	Sediment (Fresh water)	0.981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.0981 mg/kg
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	STP	71.7 mg/L	Fresh water	0.36 mg/L
	Soil	1.06 mg/kg	Marine water	0.036 mg/L
	Intermittent	0.493 mg/L	Sediment (Fresh water)	6.37 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.637 mg/kg
Butanone oxime CAS: 96-29-7 EC: 202-496-6	STP	177 mg/L	Fresh water	0.256 mg/L
	Soil	Non-applicable	Marine water	Non-applicable
	Intermittent	0.118 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	STP	0.37 mg/L	Fresh water	0.00051 mg/L
	Soil	7.9 mg/kg	Marine water	0.00236 mg/L
	Intermittent	Non-applicable	Sediment (Fresh water)	9.5 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	9.5 mg/kg
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	STP	463 mg/L	Fresh water	8.8 mg/L
	Soil	3.13 mg/kg	Marine water	0.88 mg/L
	Intermittent	9.1 mg/L	Sediment (Fresh water)	34.6 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	Non-applicable
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	STP	4168 mg/L	Fresh water	19 mg/L
	Soil	2.74 mg/kg	Marine water	1.9 mg/L
	Intermittent	190 mg/L	Sediment (Fresh water)	70.2 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7.02 mg/kg



8.2 Exposure controls:

A.- General security and hygiene measures in the work place



As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.



B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2001+A1:2009	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.





C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374.

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against liquid splash		EN 166:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Bodily protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2001 EN ISO 14116:2008/AC:2009 EN 1149-5:2008	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN 13287:2008 EN ISO 20345:2011	Replace boots at any sign of deterioration.



F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

It is not necessary to take additional emergency measures.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	48.68 % weight
V.O.C. density at 20 °C:	511.17 kg/m ³ (511.17 g/L)
Average carbon number:	8.05
Average molecular weight:	109.02 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Color:	Tintometric system
Odor:	Aromatic

Volatility:

Boiling point at atmospheric pressure:	140 °C
Vapour pressure at 20 °C:	737 Pa
Vapour pressure at 50 °C:	4041 Pa (4 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	950 - 1150 kg/m ³
Relative density at 20 °C:	0.95 - 1.15
Dynamic viscosity at 20 °C:	341 - 391 cP
Kinematic viscosity at 20 °C:	348 cSt
Kinematic viscosity at 40 °C:	>20.5 cSt
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Immiscible
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Flammability:

Flash Point:	25 - 27 °C
Autoignition temperature:	200 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

9.2 Other information:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Precaution

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Precaution	Avoid direct impact	Not applicable	Avoid alkalis or strong bases. Can react violently

10.6 Hazardous decomposition products:

In case of prolonged thermal treatment at temperatures greater than 200 °C, the decomposition products are aromatic amines (3,3' - dichlorobenzidine)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. With possibility of effects that are hazardous to the health, it is recommended not to breathe the vapours for long periods of time.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification		Acute toxicity	Genus
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17.2 mg/L (4 h)	Rat
Aluminium powder (stabilised) CAS: 7429-90-5 EC: 231-072-3	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L (4 h)	
Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w) CAS: Non-applicable EC: 918-668-5	LD50 oral	3492 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	6193 mg/L (4 h)	Rat
Isobutanol CAS: 78-83-1 EC: 201-148-0	LD50 oral	3350 mg/kg	Rat
	LD50 dermal	2460 mg/kg	Rabbit
	LC50 inhalation	24.6 mg/L (4 h)	Rat
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23.4 mg/L (4 h)	Rat
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	LD50 oral	2043 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	
Butanone oxime CAS: 96-29-7 EC: 202-496-6	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	>20 mg/L	

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification		Acute toxicity		Genus
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	LD50 oral	>2000 mg/kg		
	LD50 dermal	>2000 mg/kg		
	LC50 inhalation	>5 mg/L		
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	LD50 oral	500 mg/kg		Rat
	LD50 dermal	1100 mg/kg		Rat
	LC50 inhalation	11 mg/L (4 h)		Rat
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LD50 oral	>2000 mg/kg		
	LD50 dermal	>2000 mg/kg		
	LC50 inhalation	>20 mg/L		

Acute Toxicity Estimate (ATE mix):

	ATE mix	Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	3428.78 mg/kg (Calculation method)	0 %
Inhalation	30.85 mg/L (4 h) (Calculation method)	0 %

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification		Acute toxicity		Species	Genus
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	LC50	13.5 mg/L (96 h)		Oncorhynchus mykiss	Fish
	EC50	0.6 mg/L (96 h)		Gammarus lacustris	Crustacean
	EC50	10 mg/L (72 h)		Skeletonema costatum	Algae
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50	42.3 mg/L (96 h)		Pimephales promelas	Fish
	EC50	75 mg/L (48 h)		Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)		Chlorella vulgaris	Algae
Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w) CAS: Non-applicable EC: 918-668-5	LC50	1 - 10 mg/L (96 h)			Fish
	EC50	1 - 10 mg/L			Crustacean
	EC50	1 - 10 mg/L			Algae
Isobutanol CAS: 78-83-1 EC: 201-148-0	LC50	2030 mg/L (96 h)		Carassius auratus	Fish
	EC50	1439 mg/L (48 h)		Daphnia magna	Crustacean
	EC50	1250 mg/L (48 h)		Scenedesmus subspicatus	Algae
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	LC50	62 mg/L (96 h)		Leuciscus idus	Fish
	EC50	73 mg/L (24 h)		Daphnia magna	Crustacean
	EC50	675 mg/L (72 h)		Scenedesmus subspicatus	Algae
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	LC50	270 mg/L (96 h)		N/A	Fish
	EC50	Non-applicable			
	EC50	Non-applicable			
Butanone oxime CAS: 96-29-7 EC: 202-496-6	LC50	843 mg/L (96 h)		Pimephales promelas	Fish
	EC50	750 mg/L (48 h)		Daphnia magna	Crustacean
	EC50	83 mg/L (72 h)		Scenedesmus subspicatus	Algae
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	LC50	0.1 - 1 mg/L (96 h)			Fish
	EC50	0.1 - 1 mg/L			Crustacean
	EC50	0.1 - 1 mg/L			Algae
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	LC50	1490 mg/L (96 h)		Lepomis macrochirus	Fish
	EC50	1815 mg/L (48 h)		Daphnia magna	Crustacean
	EC50	911 mg/L (72 h)		Pseudokirchneriella subcapitata	Algae
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LC50	10000 mg/L (96 h)		Pimephales promelas	Fish
	EC50	1919 mg/L (48 h)		Daphnia magna	Crustacean
	EC50	Non-applicable			

12.2 Persistence and degradability:

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability			Biodegradability
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
Isobutanol CAS: 78-83-1 EC: 201-148-0	BOD5	0.4 g O2/g	Concentration	100 mg/L
	COD	2.41 g O2/g	Period	14 days
	BOD5/COD	0.17	% Biodegradable	90 %
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	0.79	% Biodegradable	84 %
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	BOD5	Non-applicable	Concentration	20 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	99 %
Butanone oxime CAS: 96-29-7 EC: 202-496-6	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	24 %
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	BOD5	0.71 g O2/g	Concentration	100 mg/L
	COD	2.2 g O2/g	Period	14 days
	BOD5/COD	0.32	% Biodegradable	96 %
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	BOD5	Non-applicable	Concentration	Non-applicable
	COD	0.00202 g O2/g	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	73 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3.15
	Potential	Low
Isobutanol CAS: 78-83-1 EC: 201-148-0	BCF	3
	Pow Log	0.76
	Potential	Low
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1.78
	Potential	Low
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	BCF	
	Pow Log	2.96
	Potential	
Butanone oxime CAS: 96-29-7 EC: 202-496-6	BCF	5
	Pow Log	0.59
	Potential	Low
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	BCF	3
	Pow Log	0.83
	Potential	Low
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	BCF	1
	Pow Log	-0.06
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Xylene (mixture of isomers) CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	5.249E+2 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption			Volatility
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	7.984E+2 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2.859E-2 N/m (25 °C)	Moist soil	Yes
Isobutanol CAS: 78-83-1 EC: 201-148-0	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2.378E-2 N/m (25 °C)	Moist soil	Non-applicable
Butyl Acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2.478E-2 N/m (25 °C)	Moist soil	Non-applicable
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	Koc	Non-applicable	Henry	2.94E-1 Pa·m ³ /mol
	Conclusion	Non-applicable	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Butanone oxime CAS: 96-29-7 EC: 202-496-6	Koc	3	Henry	Non-applicable
	Conclusion	Very High	Dry soil	Non-applicable
	Surface tension	2.57E-2 N/m (25 °C)	Moist soil	Non-applicable
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Koc	8	Henry	1.621E-1 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	No
	Surface tension	2.729E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP4 Irritant — skin irritation and eye damage, HP6 Acute Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2015 and RID 2015:

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: III
14.5 Dangerous for the environment: No
14.6 Special precautions for user
 Special regulations: 163, 367, 640E, 650
 Tunnel restriction code: D/E
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 37-14:



- 14.1 UN number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: III
14.5 Dangerous for the environment: No
14.6 Special precautions for user
 Special regulations: 163, 223, 955
 EmS Codes: F-E, S-E
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2015:



- 14.1 UN number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: III
14.5 Dangerous for the environment: No
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 15: REGULATORY INFORMATION (continued)

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EU) N° 453/2010, Regulation (EC) N° 2015/830)

Modifications related to the previous security card which concerns the ways of managing risks. :

COMPOSITION/INFORMATION ON INGREDIENTS:

- Added Content
 - 2-ethylhexanoic acid, zirconium salt (22464-99-9)
- Removed Content
 - Methanol (67-56-1)
 - Solvent naphtha (petroleum), light arom. < 0.1 % EC 200-753-7 (64742-95-6)
 - Hydrocarbons, C10-C13, isoalkanes, cyclics, aromatics < 2%

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation
H317: May cause an allergic skin reaction
H412: Harmful to aquatic life with long lasting effects
H226: Flammable liquid and vapour
H319: Causes serious eye irritation

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) n° 1272/2008:

- CONTINUED ON NEXT PAGE -

URKI-FLEX MET
Solvent based Mixing System Products
Colour (Group 0)

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled
Acute Tox. 4: H312 - Harmful in contact with skin
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled
Acute Tox. 4: H332 - Harmful if inhaled
Aquatic Acute 1: H400 - Very toxic to aquatic life
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
Carc. 2: H351 - Suspected of causing cancer
Eye Dam. 1: H318 - Causes serious eye damage
Eye Irrit. 2: H319 - Causes serious eye irritation
Flam. Liq. 2: H225 - Highly flammable liquid and vapour
Flam. Liq. 3: H226 - Flammable liquid and vapour
Flam. Sol. 1: H228 - Flammable solid
Repr. 2: H361 - Suspected of damaging fertility or the unborn child
Repr. 2: H361d - Suspected of damaging the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation
Skin Sens. 1: H317 - May cause an allergic skin reaction
Skin Sens. 1A: H317 - May cause an allergic skin reaction
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure
STOT SE 3: H335 - May cause respiratory irritation
STOT SE 3: H336 - May cause drowsiness or dizziness
Water-react. 2: H261 - In contact with water releases flammable gases

Classification procedure:

Skin Irrit. 2: Calculation method
Skin Sens. 1A: Calculation method
Aquatic Chronic 3: Calculation method
Flam. Liq. 3: Calculation method (2.6.4.3)
Eye Irrit. 2: Calculation method

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://esis.jrc.ec.europa.eu>
<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
CL50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -