

**E-750**

ACCELERATOR FOR ACRYLICS-POLYURETHANES

Edition: 020 2012/09

Cod: 800000750.00000.020

**APPLICATION****"USE ONLY IN INDUSTRIAL FACILITIES"**

E-750 has been formulated to reduce drying times of 2K acrylic and poliurethane products without any loss of the paint properties. Not to be used in epoxi nature products.

**PHYSICAL PROPERTIES**

Density at 20°C (g/cc)	0,87 ± 0,02
V.O.C. (g/l)	863
Flash Point	21-55°C Method: closed cup
Boiling point (°C)	> 35°C
Type of product	Accelerator additive
Colour	Clear and colourless

**APPLICATION INSTRUCTIONS**

Add in between 1 and 3% of the total amount of paint.

Not recommended as a preventive measure. Adding more than the advised % may reduce pot life of the mixing and cause loss of gloss, worse levelling, pinholes,...

The additive must be poured onto the A component or onto the A+B mixing just before the application. Not advised onto the hardener as there may be stability problems in the part of the hardener not used.

**FEATURES OF DRY FILM**

-	Accelerating effects.
---	-----------------------

**COMPOSITION**

Type of product	Aromatic hydrocarbons/ Organic tin salt
-----------------	---

**STORAGE**

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended.

Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.