



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK).

Version: 04

Revision: 19.05.2016
(Previous revision None)

Print date: 19.05.2016

1. SECTION 1: Identification of the substance/mixture and of the company/undertaking;

1.1 Product Identifier;

Product Name Compliant 2K HS Ready Mixed Colour – Matt Black

Product Code: 0621

Product Synonyms:

1.2 Relevant identified uses of the substance or mixture and uses advised against;

Product use Professional use only. Used by spraying.

**Use of the
Substance/mixture** Coating.

1.3 Details of the supplier of the safety data sheet;

Churchill Paints Ltd
Riverdane Road, Eaton Bank Trading Estate,
Congleton, Cheshire, CW12 1PN
Tel. +44(0)1260 290666, Fax. +44(0)1260 290 444

**e-mail address of
person responsible
for this SDS** sales@churchill-paints.co.uk

1.4 Emergency Telephone Number:

+44(0) 1260 290 666 (office hours only)

2. SECTION 2: Hazards identification;

2.1 Classification of the substance or mixture;

Product definition Mixture

Classification In accordance with the Classification, Labelling and Packaging Regulation (EC) No 1272/2008

Physical hazards Flam. Liq. 3, H226

Health hazard Skin Irrit. 2, H315



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

Environmental hazards

Not classified.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 16 for the full text of the H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word

Warning

Hazard statements

H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.

Precautionary Statements

Prevention

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280 – Wear protective gloves/protective clothing/eye protection/face protection.

Response

P302 + P352 – IF ON SKIN: wash with plenty of water.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage

P403 + P235 – Store in a well-ventilated place. Keep cool.

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant.

Hazardous Ingredients

1330-20-7 Xylene

Supplemental label elements

Not applicable.

Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances,



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

mixtures and articles.

Not applicable

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

3. SECTION 3: Composition/information on ingredients

3.2 Mixtures

Mixture

<i>REACH Registration Number</i>	<i>Chemical name</i>	<i>% by wt.</i>	<i>CAS No.</i>	<i>EC No. (EINEC S)</i>	<i>Index No.</i>	<i>Classification Regulation (EC) No.1272/2008 [CLP]</i>
01-2119475791-29	2-Methoxy-1-methylethyl acetate	≥ 10 - < 25	108-65-6	203-603-9	607-195-00-7	Flam. Liq. 3, H226
01-2119488216-32	Xylene (mixture of isomers)	≥ 10 - < 25	1330-20-7	215-535-7	601-022-00-9	Acute Tox. 4, H312+H332 Flam. Liq. 3, H226 Skin Irrit. 2, H315
01-2119489370-35	Ethylbenzene	≥ 2.5 - < 5	100-41-4	202-849-4	601-023-00-4	Flam. Liq. 2, H225; Acute Tox. 4, H332; STOT RE 2, H373; Asp. Tox. 1, H304
01-2119485493-29	n-Butyl Acetate Butyl ethanoate	≥ 1 - < 2.5	123-86-4	204-658-1	607-025-00-1	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066

The Full Text for all Hazard Statements on this SDS is displayed in Section 16.

4. SECTION 4: First aid measures

4.1. Description of first aid measures

Eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation

If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration or oxygen by trained personnel. Get medical attention immediately.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion

If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2. *Most important symptoms and effects, both acute and delayed*

Eye contact

No known significant effects or critical hazards.

Inhalation

There may be irritation of the throat with a feeling of tightness in the chest. There may be a feeling of tightness in the chest with shortness of breath.

Skin contact

Defatting to the skin. May cause skin dryness and irritation.

Ingestion

Severe poisoning can cause unconsciousness and severe and persistent nausea and vomiting.

Delayed / immediate effects

There may be drowsiness, slurred speech, muscular weakness, muscle twitching, tremor, blurred vision, dilated pupils and shock. There may be vomiting and diarrhoea.

4.3. *Indication of any immediate medical attention and special treatment needed*

Notes to physician

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Immediate / special treatment:

Eye bathing equipment should be available on the premises.

5. SECTION 5: Firefighting measures

5.1. *Extinguishing media*

Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Alcohol resistant foam.

Unsuitable extinguishing media

Do not use water jet.

5.2. *Special hazards arising from the substance or mixture*



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

Hazards from the Mixture

Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Run-off to sewer may create fire or explosion hazard.

Hazardous combustion products

Decomposition products may include the following materials:

Carbon dioxide
Carbon monoxide

5.3. *Advice for firefighters*

Protective actions during firefighting

Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire-exposed containers cool and disperse vapours. Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

6. **SECTION 6: Accidental release measures**

6.1. *Personal precautions, protective equipment and emergency procedures*

For non-emergency Personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Isolate leaks providing there is no additional risk to those performing this task. Personal protection equipment must be used to avoid direct contact with the spillage. Shut off all ignition sources. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK****6.2. Environmental precautions**

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up**Small spill**

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4. Reference to other sections

See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

7. SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1. Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Not available.

8. SECTION 8: Exposure Controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1. Control parameters

<i>Occupational exposure limits to be monitored in the work environment</i>					
<i>Ingredient name:</i>	<i>Comment (from EH40)</i>	<i>Time-weighted average – 8 hrs (TWA).</i>		<i>Short-term exposure limits – 15min (STELs)</i>	
		<i>ppm.</i>	<i>mg/m³</i>	<i>ppm.</i>	<i>mg/m³</i>
2-Methoxy-1-Methylethyl Acetate (PMA)	Sk	50	274	100	548
Xylene (mixture of isomers)	Sk	50	220	100	441
Ethylbenzene	Sk	100	441	125	552
n-Butyl Acetate		150	724	200	966

Comments are from HSE Guidance Note EH40/2005 Workplace exposure limits (WELs)

Sk : Can be absorbed through skin



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

DNELs (Workers)

<i>Ingredient name:</i>	<i>Exposure</i>	<i>Short term</i>		<i>Long term</i>	
		<i>Systemic</i>	<i>Local</i>	<i>Systemic</i>	<i>Local</i>
2-Methoxy-1-methylethyl acetate (PMA)	<i>Oral</i>	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	<i>Dermal</i>	Non-applicable	Non-applicable	153.5 mg/kg	Non-applicable
	<i>Inhalation</i>	Non-applicable	Non-applicable	275 mg/m ³	Non-applicable
Xylene (mixture of isomers)	<i>Oral</i>	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	<i>Dermal</i>	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	<i>Inhalation</i>	289 mg/m ³	289 mg/m ³	77 mg/m ³	Non-applicable
Ethylbenzene	<i>Oral</i>	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	<i>Dermal</i>	Non-applicable	Non-applicable	180 mg/kg bw/day	Non-applicable
	<i>Inhalation</i>	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
n-Butyl Acetate	<i>Oral</i>	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	<i>Dermal</i>	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	<i>Inhalation</i>	960 mg/m ³	960 mg/m ³	480 mg/m ³	480 mg/m ³



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

DNELs (General Population)

<i>Ingredient name:</i>	<i>Exposure</i>	<i>Short term</i>		<i>Long term</i>	
		<i>Systemic</i>	<i>Local</i>	<i>Systemic</i>	<i>Local</i>
2-Methoxy-1-methylethyl acetate (PMA)	<i>Oral</i>	Non-applicable	Non-applicable	1.67 mg/kg	Non-applicable
	<i>Dermal</i>	Non-applicable	Non-applicable	54.8 mg/kg	Non-applicable
	<i>Inhalation</i>	Non-applicable	Non-applicable	33 mg/m ³	Non-applicable
Xylene (mixture of isomers)	<i>Oral</i>	Non-applicable	Non-applicable	1.6 mg/kg bw/day	Non-applicable
	<i>Dermal</i>	Non-applicable	Non-applicable	108 mg/Kg bw/day	Non-applicable
	<i>Inhalation</i>	174 mg/m ³	174 mg/m ³	14.8 mg/m ³	Non-applicable
Ethylbenzene	<i>Oral</i>	Non-applicable	Non-applicable	1.6 mg/Kg bw/day	Non-applicable
	<i>Dermal</i>	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	<i>Inhalation</i>	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
n-Butyl Acetate	<i>Oral</i>	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	<i>Dermal</i>	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	<i>Inhalation</i>	859.7 mg/m ³	859.7 mg/m ³	102.34 mg/m ³	102.34 mg/m ³



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

PNEC

<i>Ingredient name:</i>	<i>Environmental sphere</i>	<i>PNEC value</i>
2-Methoxy-1-methylethyl acetate (PMA)	<i>Fresh water</i>	0.635 mg/L
	<i>Marine water</i>	0.0635 mg/L
	<i>Fresh water sediment</i>	3.29 mg/kg
	<i>Marine water sediment</i>	0.329 mg/kg
	<i>Sewage Treatment</i>	100 mg/L
	<i>Soil</i>	0.29 mg/kg
Xylene (mixture of isomers)	<i>Fresh water</i>	0.327 mg/L
	<i>Marine water</i>	0.327 mg/L
	<i>Fresh water sediment</i>	12.46 mg/kg
	<i>Marine water sediment</i>	12.46 mg/kg
	<i>Sewage Treatment</i>	6.58 mg/L
	<i>Soil</i>	2.31 mg/kg
Ethylbenzene	<i>Fresh water</i>	0.1 mg/L
	<i>Marine water</i>	0.01 mg/L
	<i>Fresh water sediment</i>	13.7 mg/kg
	<i>Marine water sediment</i>	No data available
	<i>Sewage Treatment</i>	9.6 mg/L
	<i>Soil</i>	2.68 mg/kg
n-Butyl Acetate	<i>Fresh water</i>	0.18 mg/L
	<i>Marine water</i>	0.018 mg/L
	<i>Fresh water sediment</i>	0.981 mg/kg
	<i>Marine water sediment</i>	0.0981 mg/kg
	<i>Sewage Treatment</i>	35.6 mg/L
	<i>Soil</i>	0.0903 mg/kg



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

8.2 Exposure controls:

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.



Skin protection

For hands, chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacture that can provide information about the breakthrough time of the glove material.

For body, Personal protective equipment should be selected based on the task being performed and the risks involved.

For feet, appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved.



Protective gloves



Overall



Safety boots

Respiratory Protection

When spraying, use air-fed respirator. Gas/vapour filter, type A: organic vapours (EN141). Self-contained breathing apparatus must be available in case of emergency.



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

<i>Physical State</i>	Liquid
<i>Colour</i>	Black
<i>Odour</i>	Characteristic
<i>Odour threshold</i>	Not available
<i>pH</i>	Not available
<i>Melting point</i>	Not available
<i>Freezing point</i>	Not available
<i>Initial boiling point</i>	140°C
<i>Boiling range</i>	Not available
<i>Flash point</i>	31°C
<i>Evaporation rate</i>	Not available
<i>Flammability (solid, gas)</i>	Not available
<i>Upper/lower Flammability or Explosive limits</i>	Not available
<i>Vapour pressure</i>	662 Pa @ 20°C
<i>Vapour density</i>	Not available
<i>Relative density</i>	1.23 – 1.33
<i>Solubility(ies)</i>	Not available
<i>Partition coefficient n-octanol/water</i>	Not available
<i>Auto-ignition temperature</i>	315°C
<i>Decomposition temperature</i>	Not available
<i>Viscosity</i>	Not available
<i>Explosive properties</i>	Not available
<i>Oxidising properties</i>	Not available



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

10. SECTION 10: Stability and reactivity

10.1 Reactivity:

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical Stability:

This product is stable.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

In a fire, hazardous decomposition products may be produced.

10.5 Incompatible materials

Keep away from: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products

Decomposition products may include the following materials: carbon monoxide, carbon dioxide and smoke.

11. SECTION 11: Toxicological information

11.1 Information on toxicological effects

<i>Ingredient name:</i>	<i>Acute toxicity test</i>	<i>Species</i>	<i>Dose</i>	<i>Exposure</i>
2-Methoxy-1-Methylethyl Acetate (PMA)	<i>Oral – LD₅₀</i>	Rat	8532 mg/kg	
	<i>Dermal – LD₅₀</i>	Rat	>2000 mg/kg	
	<i>Inhalation – LC₅₀</i>	Rat	4345 ppm	6 hrs
Xylene (mixture of isomers)	<i>Oral – LD₅₀</i>	Rat	>3500 mg/kg	
	<i>Dermal – LD₅₀</i>	Rabbit	>4200 mg/kg	
	<i>Inhalation – LC₅₀</i>	Rat	>20 mg/L	4 hrs
Ethylbenzene	<i>Oral – LD₅₀</i>	Rat	3500 mg/kg bw	
	<i>Dermal – LD₅₀</i>	Rabbit	>5000 mg/kg bw	
	<i>Inhalation – LC₅₀</i>	Rabbit	4000 ppm	4 hrs



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

n-Butyl Acetate	<i>Oral – LD₅₀</i>	Rat	>10700 mg/kg	
	<i>Dermal – LD₅₀</i>	Rabbit	17600 mg/kg	
	<i>Inhalation – LC₅₀</i>	Rat	>21 mg/L	4 hrs

***Skin corrosion/
irritation***

The product may be absorbed through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin.

***Serious eye
damage/irritation***

The liquid splashed in the eyes may cause irritation and reversible damage.

***Respiratory or
skin sensitization***

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

***Germ cell
mutagenicity***

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

Carcinogenicity

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

Reproductive toxicity

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

***Specific target
organ toxicity -
single exposure***

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for the effects mentioned. For more information see section 3.

***Specific target
organ toxicity -
repeated exposure***

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for the effects mentioned. For more information see section 3.

Aspiration hazard

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for the effect mentioned. For more information see section 3.



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

12. SECTION 12: Ecological Information

12.1. Toxicity

<i>Ingredient name:</i>	<i>Acute toxicity test</i>	<i>Genus - Species</i>	<i>Dose</i>	<i>Exposure</i>
2-Methoxy-1-Methylethyl Acetate (PMA)	<i>LC₅₀</i>	Fish – Pimephales promelas	161 mg/L	96 hrs
	<i>EC₅₀</i>	Invertebrates - Daphnia sp.	481 mg/L	48 hrs
	<i>EC₅₀</i>	No data available		
Xylene (mixture of isomers)	<i>LC₅₀</i>	Fish - Oncorhynchus mykiss	13.5 mg/L	96 hrs
	<i>EC₅₀</i>	Crustacean - Gammarus lacustris	0.6 mg/L	96 hrs
	<i>EC₅₀</i>	Algae – Skeletonema costatum	10 mg/L	72 hrs
Ethylbenzene	<i>LC₅₀</i>	Fish	4.2 mg/L	96 hrs
	<i>EC₅₀</i>	Crustacean - Daphnia magna (Water flea)	2.93 mg/L	48 hrs
	<i>EC₅₀</i>	Algae	7.2 mg/L	48 hrs
n-Butyl Acetate	<i>LC₅₀</i>	Fish - Lepomis macrochirus (Bluegill)	100 mg/L	96 hrs
	<i>EC₅₀</i>	Invertebrates - Daphnia magna (Water flea)	44 mg/L	48 hrs
	<i>EC₅₀</i>	Algae – Desmodesmus subspicatus (Scenedesmus subspicatus)	674.7 mg/L	72 hrs

12.2. Persistence and degradability

<i>Ingredient name:</i>	<i>Concentration</i>	<i>Duration of test</i>	<i>% Biodegradability</i>
2-Methoxy-1-Methylethyl Acetate (PMA)	785 mg/L	8 days	100
Xylene (mixture of isomers)			Readily biodegradable
Ethylbenzene	22 mg/L	28 days	70



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

n-Butyl Acetate		28 days	83
-----------------	--	---------	----

12.3. Bioaccumulative potential

<i>Ingredient name:</i>	<i>BCF</i>	<i>Log P_{ow}</i>	<i>Potential</i>
2-Methoxy-1-Methylethyl Acetate (PMA)	No data available	0.43	Low
Xylene (mixture of isomers)	25.9	3.2	Low
Ethylbenzene	1	3.15	Low
n-Butyl Acetate	No data available	1.78	Low

12.4. Mobility in soil

<i>Ingredient name:</i>	<i>K_{oc}</i>	<i>HLC</i> <i>(Henry's law constant)</i>	<i>Surface tension</i>
2-Methoxy-1-Methylethyl Acetate (PMA)	No data available	No data available	No data available
Xylene (mixture of isomers)	202	524.9 Pa.m ³ /mol	No data available
Ethylbenzene	446.1	800 Pa m ³ /mol @ 25°C	No data available
n-Butyl Acetate	No data available	No data available	No data available

12.5. Results of PBT and vPvB assessment

This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

No known significant effects or critical hazards.



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

13. SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods The generation of waste should be avoided or minimised wherever possible. Disposal of this product, should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

European waste catalogue (EWC)

<i>Waste code</i>	<i>Description</i>
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances.

Packaging

<i>Waste code</i>	<i>Description</i>
15 01 04	Metallic cans

14. SECTION 14: Transport information

		<i>Land</i>	<i>Inland Waterways</i>	<i>Sea</i>	<i>Air</i>
		<i>ADR/RID</i>	<i>ADN</i>	<i>IMDG</i>	<i>ICAO</i>
14.1.	<i>UN number</i>	UN1263	UN1263	UN1263	UN1263
14.2.	<i>UN proper shipping name</i>	Paint related material	Paint related material	Paint related material	Paint related material
14.3.	<i>Transport hazard class(es)</i>	3	3	3	3
14.4.	<i>Packing group</i>	III	III	III	III
14.5.	<i>Environmental hazards</i>				
	<i>Environmentally hazardous</i> -----	No	No	-	No
	<i>Marine pollutant</i> -----	-	-	No	-



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

14.6	<i>Special precautions for user</i>				
	<i>Special regulations</i>	163, 367, 640E, 650		163, 223, 944, 955	
	<i>Tunnel restriction code</i>	D/E			
	<i>EmS codes</i>			F-E, S-E	
	<i>Physico-chemical properties</i>	See section 9		See section 9	See section 9
	<i>Limited quantities</i>	5L		5L	
	<i>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</i>	Non-applicable		Non-applicable	Non-applicable

15. SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation.

None of the ingredients of this mixture are listed in Annex XIV.

Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

Not applicable.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

16. SECTION 16: Other information

This safety data sheet conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830.

Abbreviations and Acronyms

DNEL	-	Derived No Effect Level
PNEC	-	Predicted No Effect Concentration
EUH statement	-	CLP-specific Hazard statement
ADR	-	European agreement concerning the international carriage of dangerous goods by road.



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

IMDG	-	International maritime dangerous goods code.
IATA	-	International Air Transport Association.
ICAO	-	International Civil Aviation Organisation.
BCF	-	Bio Concentration Factor
LD ₀	-	Dose at which no individuals are expected to die
LD ₅₀	-	Lethal Dose 50
LC	-	Lethal Concentration
LC ₅₀	-	Lethal Concentration 50
EC ₅₀	-	Effective Concentration 50
Log P _{ow}	-	Octanol-water partition coefficient
K _{oc}	-	Partition coefficient of organic carbon

Full Text of Physical Hazards

H226 - Flammable liquid and vapour.

Full Text of Health Hazards

H315 - Causes skin irritation.

Full Text of Environmental Hazards

Not classified.

Full Text of CLP/GHS Classifications

Flam. Liq. 2	H225	FLAMMABLE LIQUIDS	Category 2
Flam. Liq. 3	H226	FLAMMABLE LIQUIDS	Category 3
Asp. Tox. 1	H304	ASPIRATION HAZARD	Category 1
Acute Tox. 4	H312	ACUTE TOXICITY (dermal)	Category 4
Skin Irrit. 2	H315	SKIN CORROSION/IRRITATION	Category 2
Acute Tox. 4	H332	ACUTE TOXICITY (inhalation)	Category 4
STOT SE 3	H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)	Category 3
STOT RE 2	H373	SPECIFIC TARGET ORGAN TOXICITY, REPEATED EXPOSURE.	Category 2

EUH066 - Repeated exposure may cause skin dryness or cracking.

About this Safety Data Sheet.

The United Nations developed a 'Globally Harmonised System' (GHS) on classification and labelling of chemicals and the CLP Regulation adopts this system across all European Union countries, including the UK.

'CLP' is the European Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Churchill safety data sheets conform to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK).

When changes are required to Safety Data Sheets, these will be highlighted in the subsequent revision with a red bar to the left hand side of the change.



COMPLIANT 2K HS READY MIXED COLOUR – MATT BLACK

Disclaimer

The information contained in this safety data sheet is based on the state of knowledge and national legislation at the time of the 'revision date' shown on page 1. Further updates to this safety data sheet, in line with changes to legislation and technical knowledge, will be available from Churchill Paints or the Churchill website. Contact Churchill Paints for the latest revision. This safety data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. It is the user's responsibility to ascertain the suitability of the product for a specific use. As the specific conditions-of-use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.
