


**URKI-SOL 88**  
**Solvents**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** URKI-SOL 88  
Solvents
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Thinner for the application of paints and varnishes. For industrial user only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
BERNARDO ECENARRO, S.A.  
Ugarte Industrialdea, 147  
20720 Azkoitia - Gipuzkoa - Spain  
Phone.: +34 943 74 28 00 -  
Fax: +34 943 74 06 03  
msds@besa.es  
http://www.besa.es
- 1.4 Emergency telephone number:** +34 943742800 (8:00-13:00) (14:30-17:30)

**SECTION 2: HAZARDS IDENTIFICATION**

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) n° 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.  
Acute Tox. 3: Acute toxicity, Category 3, H301+H311+H331  
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412  
Asp. Tox. 1: Aspiration hazard, Category 1, H304  
Eye Irrit. 2: Eye irritation, Category 2, H319  
Flam. Liq. 2: Flammable liquids, Category 2, H225  
Repr. 2: Reproductive toxicity, Category 2, H361d  
Skin Irrit. 2: Skin irritation, Category 2, H315  
STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373  
STOT SE 1: Specific target organ toxicity — single exposure, Category 1, H370
- 2.2 Label elements:**  
**CLP Regulation (EC) n° 1272/2008:**  
**Danger**
- 
- Hazard statements:**  
Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways  
Eye Irrit. 2: H319 - Causes serious eye irritation  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour  
Repr. 2: H361d - Suspected of damaging the unborn child.  
Skin Irrit. 2: H315 - Causes skin irritation  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure  
STOT SE 1: H370 - Causes damage to organs
- Precautionary statements:**  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313: IF exposed or concerned: Get medical advice/attention  
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
- Supplementary information:**  
EUH066: Repeated exposure may cause skin dryness or cracking
- Substances that contribute to the classification**

- CONTINUED ON NEXT PAGE -

**URKI-SOL 88**  
**Solvents**

**SECTION 2: HAZARDS IDENTIFICATION (continued)**

Methanol; Toluene; Acetone; Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w)

**2.3 Other hazards:**

Non-applicable

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**

Non-applicable

**3.2 Mixture:**

**Chemical description:** Mixture composed of organic substances

**Components:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 67-56-1 EC: 200-659-6 Index: 603-001-00-X REACH: 01-2119433307-44-XXXX	<b>Methanol</b> Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger	ATP CLP00 25 - <50 %
CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51-XXXX	<b>Toluene</b> Regulation 1272/2008 Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	ATP CLP00 25 - <50 %
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX	<b>Acetone</b> Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	ATP CLP00 10 - <25 %
CAS: Non-applicable EC: 918-668-5 Index: Non-applicable REACH: 01-2119455851-35-XXXX	<b>Hydrocarbons, C9, aromatics (Benzene &lt; 0.1 % w/w)</b> Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336 - Danger	Self-classified 10 - <25 %
CAS: 79-20-9 EC: 201-185-2 Index: 607-021-00-X REACH: 01-2119459211-47-XXXX	<b>Methyl Acetate</b> Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	ATP CLP00 5 - <10 %
CAS: 115-10-6 EC: 204-065-8 Index: 603-019-00-8 REACH: 01-2119472128-37-XXXX	<b>Dimethyl ether</b> Regulation 1272/2008 Flam. Gas 1: H220; Press. Gas: H280 - Danger	ATP CLP00 <0,2 %
CAS: 109-99-9 EC: 203-726-8 Index: 603-025-00-0 REACH: 01-2119444314-46-XXXX	<b>Tetrahydrofuran</b> Regulation 1272/2008 Carc. 2: H351; Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H335 - Danger	ATP ATP03 <0,2 %

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

**Other information:**

Identification	Specific concentration limit
Methanol CAS: 67-56-1 EC: 200-659-6	% (w/w) >=10: STOT SE 1 - H370 3<= % (w/w) <10: STOT SE 2 - H371
Tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	% (w/w) >=25: Eye Irrit. 2 - H319 % (w/w) >=25: STOT SE 3 - H335

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

Request medical assistance immediately, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

- CONTINUED ON NEXT PAGE -

**URKI-SOL 88**  
**Solvents**

**SECTION 4: FIRST AID MEASURES (continued)**

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

- CONTINUED ON NEXT PAGE -

**URKI-SOL 88**  
**Solvents**

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in fixed places that comply with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

Minimum Temp.: 5 °C  
Maximum Temp.: 30 °C  
Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the work environment

Identification	Environmental limits	
	IOELV (8h)	IOELV (STEL)
Methanol CAS: 67-56-1 EC: 200-659-6	200 ppm	260 mg/m <sup>3</sup>
Acetone CAS: 67-64-1 EC: 200-662-2	500 ppm	1210 mg/m <sup>3</sup>
Toluene CAS: 108-88-3 EC: 203-625-9	50 ppm	192 mg/m <sup>3</sup>
Tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	100 ppm	384 mg/m <sup>3</sup>
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	1000 ppm	1920 mg/m <sup>3</sup>

**DNEL (Workers):**

- CONTINUED ON NEXT PAGE -

**URKI-SOL 88**  
**Solvents**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Methanol CAS: 67-56-1 EC: 200-659-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	40 mg/kg	Non-applicable	40 mg/kg	Non-applicable
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
	Inhalation	384 mg/m <sup>3</sup>	384 mg/m <sup>3</sup>	192 mg/m <sup>3</sup>	192 mg/m <sup>3</sup>
Acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable
	Inhalation	Non-applicable	2420 mg/m <sup>3</sup>	1210 mg/m <sup>3</sup>	Non-applicable
Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w) CAS: Non-applicable EC: 918-668-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	150 mg/m <sup>3</sup>	Non-applicable
Methyl Acetate CAS: 79-20-9 EC: 201-185-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	88 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	610 mg/m <sup>3</sup>	305 mg/m <sup>3</sup>
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1894 mg/m <sup>3</sup>	Non-applicable
Tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Inhalation	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	150 mg/m <sup>3</sup>	150 mg/m <sup>3</sup>

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Methanol CAS: 67-56-1 EC: 200-659-6	Oral	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable
	Dermal	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable
	Inhalation	50 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Non-applicable	Non-applicable	8.13 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
	Inhalation	226 mg/m <sup>3</sup>	226 mg/m <sup>3</sup>	56.5 mg/m <sup>3</sup>	56.5 mg/m <sup>3</sup>
Acetone CAS: 67-64-1 EC: 200-662-2	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	200 mg/m <sup>3</sup>	Non-applicable
Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w) CAS: Non-applicable EC: 918-668-5	Oral	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	32 mg/m <sup>3</sup>	Non-applicable
Methyl Acetate CAS: 79-20-9 EC: 201-185-2	Oral	Non-applicable	Non-applicable	44 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	44 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	131 mg/m <sup>3</sup>	152 mg/m <sup>3</sup>
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	471 mg/m <sup>3</sup>	Non-applicable
Tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
	Inhalation	150 mg/m <sup>3</sup>	150 mg/m <sup>3</sup>	62 mg/m <sup>3</sup>	75 mg/m <sup>3</sup>

**PNEC:**

Identification				
Methanol CAS: 67-56-1 EC: 200-659-6	STP	100 mg/L	Fresh water	154 mg/L
	Soil	23.5 mg/kg	Marine water	15.4 mg/L
	Intermittent	1540 mg/L	Sediment (Fresh water)	570.4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

- CONTINUED ON NEXT PAGE -

**URKI-SOL 88**  
**Solvents**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification				
Toluene CAS: 108-88-3 EC: 203-625-9	STP	13.61 mg/L	Fresh water	0.68 mg/L
	Soil	2.89 mg/kg	Marine water	0.68 mg/L
	Intermittent	0.68 mg/L	Sediment (Fresh water)	16.39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16.39 mg/kg
Acetone CAS: 67-64-1 EC: 200-662-2	STP	100 mg/L	Fresh water	10.6 mg/L
	Soil	29.5 mg/kg	Marine water	1.06 mg/L
	Intermittent	21 mg/L	Sediment (Fresh water)	30.4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3.04 mg/kg
Methyl Acetate CAS: 79-20-9 EC: 201-185-2	STP	600 mg/L	Fresh water	0.12 mg/L
	Soil	0.0416 mg/kg	Marine water	0.012 mg/L
	Intermittent	1.2 mg/L	Sediment (Fresh water)	0.128 mg/kg
	Oral	20.4 g/kg	Sediment (Marine water)	0.0128 mg/kg
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	STP	160 mg/L	Fresh water	0.155 mg/L
	Soil	0.045 mg/kg	Marine water	0.016 mg/L
	Intermittent	1.549 mg/L	Sediment (Fresh water)	0.681 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.069 mg/kg
Tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	STP	4.6 mg/L	Fresh water	4.32 mg/L
	Soil	2.13 mg/kg	Marine water	0.432 mg/L
	Intermittent	21.6 mg/L	Sediment (Fresh water)	23.3 mg/kg
	Oral	67 g/kg	Sediment (Marine water)	2.33 mg/kg



**8.2 Exposure controls:**

**A.- General security and hygiene measures in the work place**



In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the professional exposure limits. In case of using individual protection equipment they should have the CE marking in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.



**B.- Respiratory protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2001+A1:2009	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

**C.- Specific protection for the hands**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves (HPPE), Breakthrough Time 480 min, thickness 0.062 mm		EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

**D.- Ocular and facial protection**





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face mask		EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Bodily protection**

- CONTINUED ON NEXT PAGE -



**URKI-SOL 88**  
**Solvents**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	 CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	 CAT III	EN 13287:2008 EN ISO 20345:2011 EN 13832-1:2006	Replace boots at any sign of deterioration.

F.- Additional emergency measures

It is not necessary to take additional emergency measures.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 100 % weight  
V.O.C. density at 20 °C: 836 kg/m<sup>3</sup> (836 g/L)  
Average carbon number: 4.23  
Average molecular weight: 68.17 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 833 kg/m<sup>3</sup> (833 g/L)  
EUlimit for the product (Cat. B.A): 850 g/L (2010)  
Components: Non-applicable

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C: Liquid  
Appearance: Fluid  
Color: Colourless  
Odor: Solvent

**Volatility:**

Boiling point at atmospheric pressure: 78 °C  
Vapour pressure at 20 °C: 12595 Pa  
Vapour pressure at 50 °C: 49767 Pa (50 kPa)  
Evaporation rate at 20 °C: Non-applicable \*

**Product description:**

Density at 20 °C: 831 - 841 kg/m<sup>3</sup>

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**URKI-SOL 88**  
**Solvents**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Relative density at 20 °C:	0.831 - 0.841
Dynamic viscosity at 20 °C:	0.55 cP
Kinematic viscosity at 20 °C:	0.66 cSt
Kinematic viscosity at 40 °C:	<20.5 cSt
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Immiscible
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
<b>Flammability:</b>	
Flash Point:	7 °C
Autoignition temperature:	240 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

**9.2 Other information:**

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Combustive materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

- CONTINUED ON NEXT PAGE -



**URKI-SOL 88**  
**Solvents**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. With possibility of effects that are hazardous to the health, it is recommended not to breathe the vapours for long periods of time.

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion (acute effect):

- Acute toxicity : Can be fatal if consumed. For more information see section 2.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Inhalation after prolonged exposure may be lethal.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Can be fatal if the product is absorbed through the skin. For more information on the secondary effects of contact with the skin see section 2.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging the unborn child.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Its ingestion, inhalation or absorption through the skin results in the risk of serious irreversible effects caused by a single exposure, not including effects which are carcinogenic, mutagenic or toxic for reproduction.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification		Acute toxicity		Genus
Methanol CAS: 67-56-1 EC: 200-659-6	LD50 oral	100 mg/kg		Rat
	LD50 dermal	300 mg/kg		Rabbit
	LC50 inhalation	3 mg/L (4 h)		Rat
Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w) CAS: Non-applicable EC: 918-668-5	LD50 oral	3492 mg/kg		Rat
	LD50 dermal	3160 mg/kg		Rabbit
	LC50 inhalation	6193 mg/L (4 h)		Rat
Acetone CAS: 67-64-1 EC: 200-662-2	LD50 oral	5800 mg/kg		Rat
	LD50 dermal	7426 mg/kg		Rabbit
	LC50 inhalation	76 mg/L (4 h)		Rat
Toluene CAS: 108-88-3 EC: 203-625-9	LD50 oral	5580 mg/kg		Rat
	LD50 dermal	12124 mg/kg		Rat
	LC50 inhalation	28.1 mg/L (4 h)		Rat

- CONTINUED ON NEXT PAGE -

**URKI-SOL 88**  
**Solvents**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

Identification	Acute toxicity	Genus	
Methyl Acetate CAS: 79-20-9 EC: 201-185-2	LD50 oral LD50 dermal LC50 inhalation	6482 mg/kg 18684 mg/kg 75 mg/L (4 h)	Rat Guinean pig Rabbit
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	LD50 oral LD50 dermal LC50 inhalation	>2000 mg/kg >2000 mg/kg 308.5 mg/L (4 h)	
Tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	LD50 oral LD50 dermal LC50 inhalation	3000 mg/kg >2000 mg/kg >20 mg/L	Rat

**Acute Toxicity Estimate (ATE mix):**

	ATE mix	Ingredient(s) of unknown toxicity
Oral	284.24 mg/kg (Calculation method)	0 %
Dermal	852.71 mg/kg (Calculation method)	0 %
Inhalation	8.53 mg/L (4 h) (Calculation method)	0 %

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:**

Identification	Acute toxicity	Species	Genus	
Methanol CAS: 67-56-1 EC: 200-659-6	LC50 EC50 EC50	15400 mg/L (96 h) 12000 mg/L (96 h) 530 mg/L (168 h)	Lepomis macrochirus Nitrocras spinipes Microcystis aeruginosa	Fish Crustacean Algae
Toluene CAS: 108-88-3 EC: 203-625-9	LC50 EC50 EC50	13 mg/L (96 h) 11.5 mg/L (48 h) 125 mg/L (48 h)	Carassius auratus Daphnia magna Scenedesmus subspicatus	Fish Crustacean Algae
Acetone CAS: 67-64-1 EC: 200-662-2	LC50 EC50 EC50	5540 mg/L (96 h) 23.5 mg/L (48 h) 3400 mg/L (48 h)	Oncorhynchus mykiss Daphnia magna Chlorella pyrenoidosa	Fish Crustacean Algae
Hydrocarbons, C9, aromatics (Benzene < 0.1 % w/w) CAS: Non-applicable EC: 918-668-5	LC50 EC50 EC50	1 - 10 mg/L (96 h) 1 - 10 mg/L 1 - 10 mg/L		Fish Crustacean Algae
Methyl Acetate CAS: 79-20-9 EC: 201-185-2	LC50 EC50 EC50	320 mg/L (96 h) 1026.7 mg/L (48 h) 120 mg/L (72 h)	Pimephales promelas Daphnia magna Scenedesmus subspicatus	Fish Crustacean Algae
Tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	LC50 EC50 EC50	2160 mg/L (96 h) Non-applicable Non-applicable	Pimephales promelas	Fish

**12.2 Persistence and degradability:**

Identification	Degradability	Biodegradability
Methanol CAS: 67-56-1 EC: 200-659-6	BOD5 COD BOD5/COD	Non-applicable Concentration 100 mg/L 1.42 g O2/g Period 14 days Non-applicable % Biodegradable 92 %
Toluene CAS: 108-88-3 EC: 203-625-9	BOD5 COD BOD5/COD	Non-applicable Concentration 100 mg/L 2.5 g O2/g Period 14 days Non-applicable % Biodegradable 100 %
Acetone CAS: 67-64-1 EC: 200-662-2	BOD5 COD BOD5/COD	Non-applicable Concentration 100 mg/L Non-applicable Period 28 days 0.96 % Biodegradable 96 %
Methyl Acetate CAS: 79-20-9 EC: 201-185-2	BOD5 COD BOD5/COD	Non-applicable Concentration 100 mg/L Non-applicable Period 14 days Non-applicable % Biodegradable 92 %

- CONTINUED ON NEXT PAGE -

**URKI-SOL 88**  
**Solvents**

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Degradability		Biodegradability	
Tetrahydrofuran	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 109-99-9	COD	Non-applicable	Period	14 days
EC: 203-726-8	BOD5/COD	Non-applicable	% Biodegradable	100 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
Methanol	BCF	3
CAS: 67-56-1	Pow Log	-0.77
EC: 200-659-6	Potential	Low
Toluene	BCF	13
CAS: 108-88-3	Pow Log	2.73
EC: 203-625-9	Potential	Low
Acetone	BCF	1
CAS: 67-64-1	Pow Log	-0.24
EC: 200-662-2	Potential	Low
Methyl Acetate	BCF	0.8
CAS: 79-20-9	Pow Log	0.18
EC: 201-185-2	Potential	Low
Tetrahydrofuran	BCF	3
CAS: 109-99-9	Pow Log	0.46
EC: 203-726-8	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
Methanol	Koc	Non-applicable	Henry	Non-applicable
CAS: 67-56-1	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-659-6	Surface tension	2.355E-2 N/m (25 °C)	Moist soil	Non-applicable
Toluene	Koc	178	Henry	6.728E+2 Pa·m <sup>3</sup> /mol
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes
EC: 203-625-9	Surface tension	2.793E-2 N/m (25 °C)	Moist soil	Yes
Acetone	Koc	1	Henry	2.929E+0 Pa·m <sup>3</sup> /mol
CAS: 67-64-1	Conclusion	Very High	Dry soil	Yes
EC: 200-662-2	Surface tension	2.304E-2 N/m (25 °C)	Moist soil	Yes
Methyl Acetate	Koc	Non-applicable	Henry	Non-applicable
CAS: 79-20-9	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 201-185-2	Surface tension	2.454E-2 N/m (25 °C)	Moist soil	Non-applicable
Dimethyl ether	Koc	Non-applicable	Henry	Non-applicable
CAS: 115-10-6	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-065-8	Surface tension	1.136E-2 N/m (25 °C)	Moist soil	Non-applicable
Tetrahydrofuran	Koc	23	Henry	7.194E+0 Pa·m <sup>3</sup> /mol
CAS: 109-99-9	Conclusion	Very High	Dry soil	Yes
EC: 203-726-8	Surface tension	2.498E-2 N/m (25 °C)	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 03 05*	Organic wastes containing dangerous substances	Dangerous

- CONTINUED ON NEXT PAGE -

**URKI-SOL 88**  
**Solvents**

**SECTION 13: DISPOSAL CONSIDERATIONS (continued)**

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP4 Irritant — skin irritation and eye damage, HP6 Acute Toxicity, HP10 Toxic for reproduction

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2015 and RID 2015:



- |   |  |
|---|--|
| <b>14.1 UN number:</b>  | UN1992                                     |
| <b>14.2 UN proper shipping name:</b>  | FLAMMABLE LIQUID, TOXIC, N.O.S. (Methanol) |
| <b>14.3 Transport hazard class(es):</b>   | 3  |
| Labels:   | 3, 6.1                                     |
| <b>14.4 Packing group:</b>  | II   |
| <b>14.5 Dangerous for the environment:</b>                                      | No   |
| <b>14.6 Special precautions for user</b>  |  |
| Special regulations:  | 274  |
| Tunnel restriction code:  | D/E  |
| Physico-Chemical properties:  | see section 9                              |
| Limited quantities:   | 1 L  |
| <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b> | Non-applicable                             |

**Transport of dangerous goods by sea:**

With regard to IMDG 37-14:



- |   |  |
|---|--|
| <b>14.1 UN number:</b>  | UN1992                                     |
| <b>14.2 UN proper shipping name:</b>  | FLAMMABLE LIQUID, TOXIC, N.O.S. (Methanol) |
| <b>14.3 Transport hazard class(es):</b>   | 3  |
| Labels:   | 3, 6.1                                     |
| <b>14.4 Packing group:</b>  | II   |
| <b>14.5 Dangerous for the environment:</b>                                      | No   |
| <b>14.6 Special precautions for user</b>  |  |
| Special regulations:  | 274  |
| EmS Codes:  | F-E, S-D                                   |
| Physico-Chemical properties:  | see section 9                              |
| Limited quantities:   | 1 L  |
| <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b> | Non-applicable                             |

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2015:

- CONTINUED ON NEXT PAGE -

**URKI-SOL 88**  
**Solvents**

**SECTION 14: TRANSPORT INFORMATION (continued)**



<b>14.1 UN number:</b>	UN1992
<b>14.2 UN proper shipping name:</b>	FLAMMABLE LIQUID, TOXIC, N.O.S. (Methanol)
<b>14.3 Transport hazard class(es):</b>	3
Labels:	3, 6.1
<b>14.4 Packing group:</b>	II
<b>14.5 Dangerous for the environment:</b>	No
<b>14.6 Special precautions for user</b>	
Physico-Chemical properties:	see section 9
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Non-applicable

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Contains more than 0.1 % of Toluene by weight. The use of this product is prohibited in adhesives or spray paints for sale to the general public.

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EU) N° 453/2010, Regulation (EC) N° 2015/830)

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

Non-applicable

**Texts of the legislative phrases mentioned in section 2:**

- CONTINUED ON NEXT PAGE -

**URKI-SOL 88**  
**Solvents**

**SECTION 16: OTHER INFORMATION (continued)**

H370: Causes damage to organs  
H412: Harmful to aquatic life with long lasting effects  
H315: Causes skin irritation  
H373: May cause damage to organs through prolonged or repeated exposure  
H361d: Suspected of damaging the unborn child.  
H301+H311+H331: Toxic if swallowed, in contact with skin or if inhaled  
H304: May be fatal if swallowed and enters airways  
H225: Highly flammable liquid and vapour  
H319: Causes serious eye irritation

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) n° 1272/2008:**

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways  
Carc. 2: H351 - Suspected of causing cancer  
Eye Irrit. 2: H319 - Causes serious eye irritation  
Flam. Gas 1: H220 - Extremely flammable gas  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour  
Flam. Liq. 3: H226 - Flammable liquid and vapour  
Press. Gas: H280 - Contains gas under pressure, may explode if heated  
Repr. 2: H361d - Suspected of damaging the unborn child.  
Skin Irrit. 2: H315 - Causes skin irritation  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure  
STOT SE 1: H370 - Causes damage to organs  
STOT SE 3: H335 - May cause respiratory irritation  
STOT SE 3: H336 - May cause drowsiness or dizziness

**Classification procedure:**

STOT SE 1: Calculation method  
Aquatic Chronic 3: Calculation method  
Skin Irrit. 2: Calculation method  
STOT RE 2: Calculation method  
Repr. 2: Calculation method  
Acute Tox. 3: Calculation method  
Asp. Tox. 1: Calculation method  
Flam. Liq. 2: Calculation method (2.6.4.3)  
Eye Irrit. 2: Calculation method

**Advice related to training:**

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://esis.jrc.ec.europa.eu>  
<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
CL50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol–water partition coefficient  
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -