



MOBIHEL®

Produced in HELIOS Tovarni barv, lakov in umetnih smol Količevo d.o.o.
Količevo 65, 1230 Domžale, Slovenija
T +386 1 722 40 00
F +386 1 722 43 10
E info@helios.si
www.helios.si

TECHNICAL DATA SHEET









MOBIHEL PE putty soft

Use: *Two-component polyester levelling out mass to even out bigger irregularities on steel sheet metal. The putty is distinguished for easy application and sanding, it is not porous (it does not cause holes after sand-blasting) and will not be reduced with time.*

Surface: - *sand-blasted and cleaned steel sheet metal*

Colour shade: *grey*

ONLY FOR PROFESSIONAL USE!

	<p><i>Pot life</i> 3,5 – 6 min. / 20°C</p>
	
	<p><i>20 – 30 min. / 20°C</i></p>
	<p><i>5 min.</i></p>
	<p><i>P 80 – 150</i></p>
	<p>FURTHER TREATMENT: <i>All 2K sealers from MOBIHEL programme.</i></p>
	<p><i>EU limit value VOC for this type of products (category II B (a)) in the form, which is ready for application is 250 g/l VOC of this product, prepared for use is 170 g/l.</i></p>
	<p><i>18 months</i></p>